

Document Title: Slick, DS-2		Part # and Rev. 18085	
		Release Date:	
Rev.	Description	Revision By	Date
Date -- Time	Added description from other slicks	Allison	6/8/16

Production Filename:

<http://publications.decagon.com/Marketing/Description%20Files/18085 Slick DS-2.pdf>

Printing Process: Digital

Size: 8.5 inches wide, 11 inches tall

Ink: 4/4 Color Both Sides

Paper: 100 lbs. book gloss coated

Page Count: 2

Proof type: soft proof

Single hole drilling: none

DS-2

Sonic Anemometer

Measure Wind Speed and Direction

The DS-2 is a sonic anemometer that measures horizontal wind speed and direction. The DS-2 is a rugged, research grade sensor.

Applications

- Characterize microclimate
- Modelling PET and ET
- Surface-atmosphere energy exchange
- Transport of mass and energy (particulate matter, gases, heat)
- Monitoring fertilizer/pesticide/herbicide applications
- Fire weather assessment, fire behavior forecasting
- Mobile sampling platforms



Accurate at Low Wind Speeds

The DS-2 has a lower measurement threshold of 0 m/s. Because of friction, cup anemometers have a lower measurement threshold of 0.5 m/s.

Never Needs Calibration

Sonic anemometers use ultrasonic sound waves to measure wind velocity. Because the measurement is founded on first principles, the sensor doesn't need calibration.

Requires No Maintenance

No moving parts means you don't have to oil or replace anything.

Uses Very Little Power

Built to run for 6 months or more on the 5 AA batteries in your Enviro series data logger (also compatible with other data loggers).

Affordable

High accuracy and low per-sensor cost make acquiring vertical wind profiles and greater spatial coverage possible.

Specifications

Wind Speed

Range: 0 to 30 m/s. Resolution: 0.05 m/s.

Accuracy: $\pm 3.0\%$ or ± 36 , whichever is larger.

Wind Direction

Range: 0 to 360 degrees. Resolution: 5 degrees.

Accuracy: ± 3 degrees.

Diameter: 100 mm. Sensor body height (w/ mount): 155 mm.

Connectivity: DS-2. Maximum operating speed: 150. Connector types: 3.5 mm stereo plug or straight 6 lined mod wire. Data logger compatibility: (not exclusive) Decagon Enviro series, Campbell Scientific.



we measure the world®

instruments@decagon.com
phone: 1.509.332.2756
www.decagon.com

©2014 Decagon Devices, Inc.
P/NW122 10 USA